

DURASHIELD-SB

WEATHERPROOF SOLVENT BASED TRANSPERENT COATING FOR BUILDINGS FACADES

PRODUCT DESCRIPTION

High performance polymer based weatherproofing coating to provide wet look to stones on building exteriors. It offers long term protection, retention of good aesthetics and retaining stone cast due to excellent UV and fungus resistance.

PRODUCT ATTRIBUTES

- It forms a smooth and durable film
- Fungus Control - Due to incorporation of highly effective broad spectrum fungicide, it offers long term protection against fungal growth.
- UV Resistance - It is completely resistant to UV radiation.
- No chalking and peeling.

PRODUCT SPECIFICATIONS

Form.....	Pasty liquid
Method of Application.....	Brush, roller or Spray
Drying Time.....	30 minutes (surface dry)2 hours (hard dry) (Depends on Relative Humidity and Temperature)
Recoating Interval.....	4 hours (minimum)
Number of Coats.....	2 coats (minimum)
Recommended	
Covering Capacity.....	5 to 6 m ² /kg for 2 coats depending on surface porosity and roughness.
Fungus Resistance.....	Resistant to fungus Shelf
Life.....	Minimum 6 months if sealed drum is not opened

METHOD OF APPLICATION

a) SURFACE PREPARATION

The surface should be washed and cleaned to remove dust, dirt, if any and laitence. All stone joints should be properly sealed with non shrink grouts or suitable sealents. The surface should be free of any oil and grease.

b) TOP COATS

Apply two or more coats of **DURASHIELD-SB** on a properly prepared surface with an intercoat interval of 4 hours.

SPECIAL INSTRUCTIONS

- Stir the contents of the drum thoroughly to disperse the settled matter.
- Do not store the drums in direct sunlight.