

DURASHIELD-WB

TRANSPARENT SEALER COATING FOR BUILDINGS FACADES

PRODUCT DESCRIPTION

High performance acrylic latex based weatherproofing sealer coating for maintaining natural look of stones on building exteriors. It offers long term protection, retention of good aesthetics and retaining stone cast due to excellent UV and fungus resistance.

PRODUCT ATTRIBUTES

- Seals the pores and forms a smooth film
- Fungus Control - Due to incorporation of highly effective broad spectrum fungicide, it offers long term protection against fungal growth.
- UV Resistance - It is completely resistant to UV radiation.
- Excellent Breathability - Coating is permeable to water vapour.
- No chalking and peeling.

PRODUCT SPECIFICATIONS

Form.....Liquid
Method of Application.....Brush, roller or
Spray
Drying Time.....30 minutes (surface
dry) 2 hours (hard dry) (Depends on Relative Humidity and Temperature)
Recoating Interval..... 4 hours
(minimum)
Covering Capacity.....6-8 m²/kg depending on surface
porosity and roughness.
Fungus Resistance.....Resistant to
fungus
Shelf Life..... Minimum 6 months if sealed drum is not
opened

METHOD OF APPLICATION

1. SURFACE PREPARATION

The surface should be washed and cleaned to remove dust, dirt, if any and laitence. All stone joints should be properly sealed with non shrink grouts or suitable sealents. The surface should be free of any oil and grease .

2. TOP COATS

Apply one coat of **DURASHIELD-WB** on a properly prepared surface for sealing the pores. If a thicker film is desired more coats may be applied.

SPECIAL INSTRUCTIONS

- * Stir the contents of the drum thoroughly to disperse the settled matter.
- * Do not store the drums in direct sunlight.